

PAPER • OPEN ACCESS

Nonstandard teeth profile description and justification of precessional gear parameters selection

To cite this article: I Bostan and V Dulgheru 2019 *IOP Conf. Ser.: Mater. Sci. Eng.* **514** 012025

View the [article online](#) for updates and enhancements.



240th ECS Meeting ORLANDO, FL

Orange County Convention Center Oct 10-14, 2021



Abstract submission due: April 9

SUBMIT NOW

Nonstandard teeth profile description and justification of precessional gear parameters selection

I Bostan¹ and V Dulgheru¹

¹Basics of Machine Design Department, Technical University of Moldova, Republic of Moldova

E-mail: valeriu.dulgheru@bpm.utm.md

Abstract. Teeth profiles have an important role in the efficient transformation of motion in the precessional transmissions. Multiple precessional gear theory, previously developed, did not take into consideration the influence of the diagram error of the linking mechanism in the processing device for gear wheel on the teeth profile. Functioning under the multiplication regime, these errors have major influence, which can lead to instant blocking of gear and to power losses. With this purpose, a thorough analysis was conducted on the motion development mechanism under multiplication, and on the teeth profile error generating source. On the basis of fundamental theory of multiple precessional gear, previously developed, a new gear with modified teeth profile and the technology for its industrial manufacturing was proposed and patented. The elaboration of the mathematic model of the modified teeth profile is based integrally on the mathematic model of teeth profile, previously developed by the authors. With this purpose it is necessary to present the detailed description of teeth profile without modification and, then, to present of the description of modified profile peculiarities.

1. Introduction

The diversity of beneficiaries' requirements concern mechanical transmissions is reduced, specially, to the increase of reliability, efficiency and to the decrease of mass and dimensions. It becomes more and more difficult to satisfy the mentions requirements by updating partially the traditional transmissions. This problem can be solved by using new types of mechanical transmissions - planetary precessional transmissions [1,2]. The absolute multiplicity of the precessional gear (up to 100% simultaneously engaged teeth pairs) provides high bearing capacity and increased kinematic accuracy, reduced dimensions and mass. In addition, large kinematic possibilities (-8...-3600), reduced acoustic emission and solution of all technological issues open advantages that are very important for the utilization of planetary precessional transmissions in various areas of machine building. The authors elaborated a large number of diagrams concern planetary precessional transmissions (for reducers, multipliers and differentials), multiple gears for power and kinematic transmissions, gear processing methods and their control, the majority of works being patented with about **190 patents**. Know-how in the elaboration of the multicouple precessional gear, manufacturing technology and control methods, and a range of precessional transmission diagrams belong to research team from the Technical University of Moldova.

The specific character of sphere-spatial (precessional motions of the precessional transmissions pinion makes impossible the utilisation of teeth classical involute profiles. This fact requires the elaboration of new profiles adequate to the sphere-spatial motion of pinion which would ensure high performances to the precessional transmission.

2. Elaboration of diagram of precessional transmissions

The elaboration of working machines driving mechanisms is based on the diagram of precessional transmissions, presented in figure 1 [1]. The rotating motion of the crank shaft 1 is transformed into sphere-spatial motion of the block pinion 2 with two teathed crowns 3 and 4, which are rolling without sliding on the immovable and driven toothed wheel teeth 5 and 6. Due to the minimum difference between the



number of teeth $Z_5 = Z_3 - 1, Z_6 = Z_4 - 1,$
 $Z_3 = Z_4 + 1, 2, 3...$ the transmission ratio is:

$$i = \pm \frac{Z_3 Z_6}{Z_5 Z_4 - Z_3 Z_6}. \quad (1)$$

The teeth of crowns 3 and 4 are manufactured in the shape of conical rollers installed on axis having the possibility to rotate round them, and the teeth of central wheel 5 and 6 have non-standard convex-concave profile.




Figure 1. Diagram of the planetary precessional transmission.

3. Parametrical equation of the tooth profile

In precessional gear the planet gear performs spherical-spatial motion around one fixed point [3,4]. It is known [Euler], that the body that performs spherical motion has three degrees of freedom. In theoretical mechanics, usually, the position of the body that performs precessional motion is defined by Euler angles.

The coordinates of the modified point D^m are:

$$\begin{aligned} X_D^m &= -\sin \delta \sin [Y_C^m \sin \theta + Z_C^m (1 - \cos \theta) \cos \psi]; \\ Y_D^m &= -Y_C^m \cos \delta + Z_C^m \sin \delta [\cos^2 \psi + \cos \theta \sin^2 \psi]; \\ Z_D^m &= -Y_C^m \sin \delta (\cos^2 \psi + \cos \theta \sin^2 \psi) - Z_C^m \cos \delta. \end{aligned} \quad (2)$$

The motion of point D^m related to the movable system linked rigidly to the semiproduct is described by the following formulas

$$\begin{aligned} X_{1D}^m &= X_D^m \cos \frac{\psi}{Z_1} - Y_D^m \sin \frac{\psi}{Z_1}; \\ Y_{1D}^m &= X_D^m \sin \frac{\psi}{Z_1} + Y_D^m \cos \frac{\psi}{Z_1}; \\ Z_{1D}^m &= Z_D^m. \end{aligned} \quad (3)$$

The coordinates of point E^m on the sphere is calculated according to the formulas:

$$\begin{aligned} X_{1E}^m &= k_2^m Z_{1E}^m + d_2^m; \\ Y_{1E}^m &= k_1^m Z_{1E}^m - d_1^m; \\ Z_{1E}^m &= \frac{(k_1^m d_1^m - k_2^m d_2^m)}{k_1^{m2} + k_2^{m2} + 1} - \frac{\sqrt{(k_1^m d_1^m - k_2^m d_2^m)^2 + (k_1^{m2} + k_2^{m2} + 1) \cdot (R_D^2 - d_1^{m2} - d_2^{m2})}}{k_1^{m2} + k_2^{m2} + 1}, \end{aligned} \quad (4)$$

$$k_1^m = \frac{X_{1D}^m \left(X_{1D}^m \dot{X}_{1D}^m + Y_{1D}^m \dot{Y}_{1D}^m \right) + Z_{1D}^m \dot{X}_{1D}^m}{Z_{1D}^m \left(X_{1D}^m \dot{Y}_{1D}^m - Y_{1D}^m \dot{X}_{1D}^m \right)};$$

where

$$k_2^m = -\frac{(k_1^m Y_{1D}^m + Z_{1D}^m)}{X_{1D}^m};$$

$$d_1^m = \frac{R_D^2 \cos \beta \dot{X}_{1D}^m}{\left(X_{1D}^m \dot{Y}_{1D}^m - X_{1D}^m \dot{Y}_{1D}^m \right)};$$

$$d_2^m = \frac{(R_D^2 \cos \beta + d_1^m Y_{1D}^m)}{X_{1D}^m}.$$

Point E^m projection on tooth sectional plane has the following coordinates:

$$\begin{aligned} X_E^{''m} &= \varepsilon^m \cdot X_{1E}^m, \\ Y_E^{''m} &= \varepsilon^m \cdot Y_{1E}^m, \\ Z_E^{''m} &= \varepsilon^m \cdot Z_{1E}^m, \end{aligned} \tag{5}$$

where

$$\varepsilon^m = \frac{D}{AX_{1E}^m + BY_{1E}^m + CZ_{1E}^m}.$$

The modified profile of the tooth is described by the equations:

$$\begin{aligned} \xi^m &= X_E^{''m} \cos \frac{\pi}{Z_1} + [R_D \cos(\delta + \theta + \beta) + Y_E^{''m}] \sin \frac{\pi}{Z_1}; \\ \zeta^m &= X_E^{''m} \sin \gamma \sin \frac{\pi}{Z_1} - [R_D \cos(\delta + \theta + \beta) + Y_E^{''m}] \sin \gamma \cos \frac{\pi}{Z_1} + \\ &+ [R_D \sin(\delta + \theta + \beta) + Z_E^{''m}] \cos \gamma. \end{aligned} \tag{6}$$

The computerised model of the planetary precessional gear on the figure 2 is presented. Based on the analytical description of teeth profiles by a system of parametric equations on spherical surface the profilograms of the selected gearing teeth have been designed in MatchCAD. The obtained profilograms are shown in figure 3, 4, 5. The analysis of the obtained teeth profiles, based on the fundamental conditions of gearing selection (high bearing capacity due to gearing multiplicity, small dimensions and mass, technology, etc.) has allowed the selection of the teeth profiles parameters.




Figure 2. Computerised model of the planetary precessional gear.

This continuing dramatically change in available computational resources offers new options in gear design for gear manufacturing processes. They include the complete 3D model of the whole gear, including the gear body and all gear flanks, obtained by using of modelling system *CATIA V5R7*.

Constructions peculiarities and high multiplicity of gear create favourable premises for the improvement of precessional transmissions kinematics accuracy. Within these activities we elaborated:

- theoretical basis for the identification of kinematics error generated by various primary error (frontal and radial knocking), on the basis of error independent action principle by fulfilling computer assisted mathematics experiment;
- compensation method for manufacturing and assembling errors;




Figure 3. The influence of the number of teeth on the form of teeth profile.




Figure 4. The influence of the number of teeth on the form of teeth profile.




Figure 5. The influence of the taper angle of the rollers, β on the form of teeth profile.

- method of determination of probable limit error for precessional reducers with account of the stochastic character of manufacturing and assembling errors.

Special attention was paid to precessional reducers experimental research. For this purpose two laboratories were set up: 1) for mechanical tests and; 2) working technology for gear wheels. The laboratories are equipped with stands for testing and with control and modern measuring devices.

Know-how in the elaboration of the multicouple precessional gear, manufacturing technology and control methods, and a range of precessional transmission diagrams belong to research team from the Technical University of Moldova. During the last 35 years the team patented about 190 inventions.

References:

- [1] Bostan, I., Dulgheru, V., Sochirean A., Babaian I. Anthology of inventions: planetary precessional transmissions. Vol.1. – Ch.: S.n., 2011. 593p. ISBN 978-9975-4100-9-0.
- [2] Bostan, I. Precessional transmissions with multicouple gear, Stiinta, Chişinău. 1992, ISBN5-376-01005-8.
- [3] Bostan, I., Dulgheru V., Vaculenco M. Precessional gear-engagement. Patent nr. 1886MD, 2001.
- [4] Bostan, I., Babaian, I. Precessional gear-engagement. Patent nr.1455094 RU (patent nr. 560 MD), 1996.

Acknowledgments

Ion Bostan, PhD.Dr.Sc.Prof., academician, Technical University of Moldova, Department “Basics of Machine Design”, E-mail: ion.bostan@cmts.utm.md Office Phone: 00373 22 509986. Home Address: Lidia Istrati 20, Str. Home Phone: 00373 22 31 92 63.

Valeriu Dulgheru, PhD.Dr.Sc.Prof., Head of Department, Technical University of Moldova, Department “Basics of Machine Design”, E-mail: valeriu.dulgheru@bpm.utm.md Office Phone: 00373 22 509939. Home Address: Lidia Istrati 23, Str. Home Phone: 00373 22 31 92 05.